

Product data sheet

Rigips connection seal felt, self-adhesive both sides



Product description: Sealant tape made of felt, both sides self-adhesive glue based on rubber with protective foil strip.

Area of application: For connections of wall and ceiling constructions to adjacent solid components made of concrete or masonry. Suitable for rear connection of Rigips C-wall profiles in double stud walls.

Technical specifications

Parameters	Sign	Value	Unit	Certification
Material				
Type of material		felt		
Building material class				
Fire behaviour		E		EN 13501-1
Dimensions				
Thickness	t	5.0	mm	
Width	w	50 / 75 / 100	mm	
Length	l	10000	mm	
Colour				
Colour		grey with coloured threads		
Notes				
Storage		Dry Air access		
Shelf Life		12 months with dry storage		
Package Size		According to Pricelist		

¹ When applied 2 times to an intact zinc surface.

² After complete hardening

³ With 1.5-fold cross application

The values listed in this product data sheet only reflect the performance characteristics of the products. In addition, gypsum plaster systems have structural and structural properties, which can be found in our system documentation (e. g. Planen und Bauen).

The information in this publication is based on our current technical knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve the users of our products from the responsibility of carrying out their own inspections and tests, as they only represent general guidelines. They neither do imply any legally binding assurance of certain properties or of suitability for a particular application. It is the responsibility of those to whom we supply our products to ensure that any proprietary rights and existing laws and regulations are observed. We reserve the right to modifications in the interests of technical advancement without prior notice.