

**DECLARATION OF PERFORMANCE**

No.: Rigips\_U\_Direktabhänger\_CD\_125\_ungebogen\_LE\_2202

- (1) *Unique identification code of the product-type*  
**Rigips U Direktabhänger CD 125 ungebogen**
- (2) *Intended use/es*  
**Suspended ceiling substructure component for indoor use in buildings  
Suspension component (EN 13964) 125 mm**
- (3) *Manufacturer*  
**Saint-Gobain Rigips GmbH  
Schanzenstr. 84  
D-40549 Düsseldorf**
- (4) *Authorised representative*  
**N/A**
- (5) *System/s of AVCP*  
**System 3 for the load bearing capacity  
System 4 for all other properties**
- (6a) *Harmonised standard*  
**EN 13964:2014**
- Notified body/ies*  
**Instytut Techniki Budowlanej (1488)  
Materialprüfungsamt Nordrhein-Westfalen MPA NRW (0432)**
- (6b) *European Assessment Document*  
**N/A**
- European Technical Assessment*  
**N/A**
- Technical Assessment Body*  
**N/A**
- Notified body/ies*  
**N/A**



(7) Declared performance/s


Essential characteristics	Performance
Reaction to fire (R2F)	A1
Load bearing capacity	400 N
Resistance to fasteners	NPD
Durability	B

(8) Appropriate Technical Documentation and/or Specific Technical Documentation  
N/A

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.


Signed for and on behalf of the manufacturer by:

Düsseldorf, 04. February 2022




---

Raimund Heintl, Managing Director




---

Dr. Benjamin Kaplan, Director R&D Isover/Rigips Germany

<b>CE</b>	
<b>Saint-Gobain Rigips GmbH</b> Schanzenstr. 84 D-40549 Düsseldorf	
13	
<b>Rigips_U_Direktabhaenger_CD_125_ungebogen_LE_2202</b> <b>EN 13964:2014</b> <b>Suspended ceiling substructure component for indoor use</b> <b>in buildings</b> <b>Suspension component (EN 13964) 125 mm</b>	
Notified body/ies: 1488, 0432	
Reaction to fire (R2F)	A1
Load bearing capacity	400 N
Resistance to fasteners	NPD
Durability	B

