



DECLARATION OF PERFORMANCE
SAINT-GOBAIN

No.: Rigips_Aussteifungsprofil_UA_50_C3-hoch_bis_C5-hoch_LE_0120

Product Type

EN 14195 : UA/40/50/40

Identification of the construction product

Rigips Aussteifungsprofil UA 50 C3-hoch bis C5-hoch
Batch identification consists of the production date printed on the label which is attached to the large profile bundle

Intended use

Metal framing component for gypsum plasterboard systems

Manufacturer

**Saint-Gobain Rigips GmbH
Schanzenstraße 84
D-40549 Düsseldorf**

Systems of assessment and verification of constancy of performance

System 4

The initial type testing according to EN 14195 was performed by the manufacturer. A factory production control system in compliance with EN ISO 9001 adapted to EN 14195 is established to ensure that the construction products conform with the declared performance characteristics.

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1	EN 14195
Yield strength	240 N/mm ²	EN 14195
Dangerous substances	NPD	EN 14195
Corrosivity category	C5-high	EN ISO 12944

SAINT-GOBAIN

The performance of the product for which this DoP has been issued is in conformity with the declared performance.
This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for and on behalf of the manufacturer by:

Dr. Benjamin Kaplan, Director R&D Isover/Rigips Germany
(name and function)

Ladenburg, 29.01.2020
(place and date of issue)



Saint-Gobain Rigips GmbH
Dr.-Albert-Reimann-Str. 20 · D-68526 Ladenburg
SAINT-GOBAIN

(signature)

Dr. Stephan Kranz, CEO

Düsseldorf, 29.01.2020
(place and date of issue)



Saint-Gobain Rigips GmbH
Schanzensir. 84 · D-40549 Düsseldorf
SAINT-GOBAIN

(signature)