



**DECLARATION OF PERFORMANCE**  
SAINT-GOBAIN

No.: Rigips\_Aussteifungsprofil\_UA\_75\_C5-hoch\_LE\_0319

*Product Type*

**EN 14195 : UA/40/75/40**

*Identification of the construction product*

**Rigips Aussteifungsprofil UA 75 C5-hoch**  
Batch identification consists of the production date printed on the label which is attached to the large profile bundle

*Intended use*

**Metal framing component for gypsum plasterboard systems**

*Manufacturer*

**Saint-Gobain Rigips GmbH  
Schanzenstraße 84  
D-40549 Düsseldorf**

*Systems of assessment and verification of constancy of performance*

**System 4**

The initial type testing according to EN 14195 was performed by the manufacturer. A factory production control system in compliance with EN ISO 9001 : 2008 adapted to EN 14195 is established to ensure that the construction products conform with the declared performance characteristics.



**Rigips**  
SAINT-GOBAIN  
*Declared performance*

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1	EN 14195
Yield strength	240 N/mm <sup>2</sup>	EN 14195
Dangerous substances	NPD	EN 14195
Corrosivity category	C5-high	EN ISO 12944

The performance of the product for which this DoP has been issued is in conformity with the declared performance.  
This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for and on behalf of the manufacturer by:

Dr. Winfried Spickermann, Head of Product Development  
(name and function)

Ladenburg, 26.03.2019  
(place and date of issue)



**Saint-Gobain Rigips GmbH**  
Dr.-Albert-Reinhold-Strasse 20 • D-68526 Ladenburg  
pka: W. Spickermann  
(signature)