

DECLARATION OF PERFORMANCE

No.: Rigips_Ankernagel_LE_2504

(1) *Unique identification code of the product-type*
Rigips_Ankernagel_LE_2504

(2) *Intended use/es*
Fasteners for use in concrete for redundant non-structural systems

(3) *Manufacturer*
SAINT-GOBAIN RIGIPS GmbH
Willstätterstraße 60
D-40549 Düsseldorf

(4) *Authorised representative*
N/A

(5) *System/s of AVCP*
System 2+

(6a) *Harmonised standard*
N/A

Notified body/ies
N/A

(6b) *European Assessment Document*
EAD 330747-00-0601

European Technical Assessment
ETA 22/0457, 01.08.2022

Technical Assessment Body
Instytut Techniki Budowlanej (ITB)

Notified body/ies
Instytut Techniki Budowlanej (ITB) (1488)

(7) Declared performance/s

| Essential characteristics | Performance |
|---|------------------------------------|
| Reaction to fire | A1 |
| Fire resistance | |
| - characteristic resistance $F_{Rk,fi}$ R30 / R60 / R90 / R120 | 0.75 / 0.75 / 0.75 / 0.6 kN |
| Characteristic spacing s_{cr} | 200 mm |
| Characteristic edge distance c_{cr} | 150 mm |
| Installation safety factor γ_{inst} | 1.4 |
| Characteristic load-bearing capacity shear load | |
| - Characteristic bending moment $M_{Rk,s}$ | 6.6 Nm |
| Characteristic resistance for all load directions | |
| - Characteristic resistance F_{Rk} | 3 kN |
| For further information, please refer directly to the ETA | |

(8) Appropriate Technical Documentation and/or Specific Technical Documentation
N/A

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Düsseldorf, 05. November 2025



Cordula Gudduschat, Managing Director



Dr. Benjamin Kaplan, Director R&D Isover/Rigips Germany



The above Declaration of Performance is valid for the following products:

Rigips Ankernagel

Template for the CE marking to be affixed to the product:

| | |
|--|--------------------------|
| CE | |
| SAINT-GOBAIN RIGIPS GmbH Willstätterstraße 60 D-40549 Düsseldorf 16 Rigips_Ankernagel_LE_2504 | |
| EAD 330747-00-0601 Fasteners for use in concrete for redundant non-structural systems &Pruefstelle_Nr& | |
| Reaction to fire | A1 |
| Fire resistance | |
| – Charakteristischer Widerstand $F_{Rk,fi}$ | 0.75 / 0.75 / 0.75 / 0.6 |
| R30 / R60 / R90 / R120 | kN |
| Characteristic spacing S_{cr} | 200 mm |
| Characteristic edge distance C_{cr} | 150 mm |
| Installation safety factor γ_{inst} | 1.4 |
| Characteristic load-bearing capacity shear load | |
| – Charakteristic bending moment $M_{Rk,s}$ | 6.6 Nm |
| Characteristic resistance for all load directions | |
| – Characteristic resistance F_{Rk} | 3 kN |
| For further information, please refer directly to the ETA | |