

## DECLARATION OF PERFORMANCE

No.: Rigips\_Feuerschutzplatte\_RFI\_impraegniert\_15\_LE\_2507

(1) *Unique identification code of the product-type*  
**Rigips\_Feuerschutzplatte\_RFI\_impraegniert\_15\_LE\_2507**

(2) *Intended use/es*  
**Gypsum board for use in buildings  
DFH2 (EN 520) 15 mm**

(3) *Manufacturer*  
**SAINT-GOBAIN RIGIPS GmbH  
Willstätterstraße 60  
D-40549 Düsseldorf**

(4) *Authorised representative*  
**N/A**

(5) *System/s of AVCP*  
**System 4**

(6a) *Harmonised standard*  
**EN 520:2004+A1:2009**

*Notified body/ies*  
**N/A**

(6b) *European Assessment Document*  
**N/A**

*European Technical Assessment*  
**N/A**

*Technical Assessment Body*  
**N/A**

*Notified body/ies*  
**N/A**

(7) Declared performance/s

| Essential characteristics                                                                                                 | Performance                                                                     |
|---------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------|
| <b>Reaction to fire</b><br>(for unprotected installation situations)                                                      | A2-s1, d0 (B)                                                                   |
| <b>Shear strength</b><br>(for stiffening of timber frame outer walls and timber roof constructions)                       | NPD                                                                             |
| <b>Bending strength</b>                                                                                                   | L/II: 650 N - T/I: 250 N                                                        |
| <b>Water vapour permeability</b><br>(to control water vapour diffusion)<br>specified as water vapour diffusion resistance | 10                                                                              |
| <b>Thermal resistance</b><br>specified as thermal conductivity                                                            | 0.25 W/(m·K)                                                                    |
| <b>Impact resistance</b><br><b>Airborne sound insulation</b><br><b>Acoustic absorption</b>                                | See system documentation of SAINT-GOBAIN RIGIPS GmbH or from the local supplier |

(8) Appropriate Technical Documentation and/or Specific Technical Documentation  
N/A

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Düsseldorf, 05. November 2025



Cordula Gudduschat, Managing Director



Dr. Benjamin Kaplan, Director R&D Isover/Rigips Germany

The above Declaration of Performance is valid for the following products:

### Rigips Feuerschutzplatte RFI imprägniert 15

Template for the CE marking to be affixed to the product:

|                                                                                                                                                                                 |                                                                                          |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|
| CE                                                                                                                                                                              |                                                                                          |
| <b>SAINT-GOBAIN RIGIPS GmbH</b><br><b>Willstätterstraße 60</b><br><b>D-40549 Düsseldorf</b><br><br><b>13</b><br><br><b>Rigips_Feuerschutzplatte_RFI_impraegniert_15_LE_2507</b> |                                                                                          |
| <b>EN 520:2004+A1:2009</b><br><br><b>Gypsum board for use in buildings</b><br><b>DFH2 (EN 520) 15 mm</b>                                                                        |                                                                                          |
| Reaction to fire<br>(for unprotected installation situations)                                                                                                                   | A2-s1, d0 (B)                                                                            |
| Bending strength                                                                                                                                                                | L/ll: 650 N - T/L: 250 N                                                                 |
| Water vapour permeability<br>(to control water vapour diffusion)<br>specified as water vapour diffusion resistance                                                              | 10                                                                                       |
| Thermal resistance<br>specified as thermal conductivity                                                                                                                         | 0.25 W/(m·K)                                                                             |
| Impact resistance<br>Airborne sound insulation<br>Acoustic absorption                                                                                                           | See system documentation of<br>SAINT-GOBAIN RIGIPS<br>GmbH or from the local<br>supplier |