

## DECLARATION OF PERFORMANCE

No.: Rigips\_Glasroc\_F\_Ridurit\_15\_LE\_2504

(1) *Unique identification code of the product-type*  
**Rigips\_Glasroc\_F\_Ridurit\_15\_LE\_2504**

(2) *Intended use/es*  
**Gypsum boards with fibrous reinforcement for the use in building construction  
GM-FH2 (EN 15283-1) 15 mm**

(3) *Manufacturer*  
**SAINT-GOBAIN RIGIPS GmbH  
Willstätterstraße 60  
D-40549 Düsseldorf**

(4) *Authorised representative*  
**N/A**

(5) *System/s of AVCP*  
**System 3 for reaction to fire  
System 4 for all other properties**

(6a) *Harmonised standard*  
**EN 15283-1:2008+A1:2009**

*Notified body/ies*  
**Prüfinstitut für das Brandverhalten von Bauprodukten Dipl.-Ing. (FH) Andreas  
Hoch (1508)**

(6b) *European Assessment Document*  
**N/A**

*European Technical Assessment*  
**N/A**

*Technical Assessment Body*  
**N/A**

*Notified body/ies*  
**N/A**

(7) Declared performance/s

Essential characteristics	Performance
<b>Reaction to fire</b> (for unprotected installation situations)	<b>A1</b>
<b>Shear strength</b> (for stiffening of timber frame outer walls and timber roof constructions)	<b>NPD</b>
<b>Flexural strength (Bending breaking load)</b>	<b>L/II: 645 N - T/L: 252 N</b>
<b>Water vapour permeability</b> (to control water vapour diffusion) specified as water vapour diffusion resistance	<b>10</b>
<b>Thermal resistance</b> specified as thermal conductivity	<b>0.25 W/(m·K)</b>
<b>Impact resistance</b> <b>Airborne sound insulation</b> <b>Acoustic absorption</b>	<b>See system documentation of SAINT-GOBAIN RIGIPS GmbH or from the local supplier</b>

(8) Appropriate Technical Documentation and/or Specific Technical Documentation  
N/A

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Düsseldorf, 05. November 2025



Cordula Gudduschat, Managing Director



Dr. Benjamin Kaplan, Director R&D Isover/Rigips Germany

The above Declaration of Performance is valid for the following products:

**Rigips Glasroc F (Ridurit) 15**

Template for the CE marking to be affixed to the product:

<b>CE</b>	
<b>SAINT-GOBAIN RIGIPS GmbH</b> <b>Willstätterstraße 60</b> <b>D-40549 Düsseldorf</b>  <b>21</b>  <b>Rigips_Glasroc_F_Ridurit_15_LE_2504</b>	
<b>EN 15283-1:2008+A1:2009</b>  <b>Gypsum boards with fibrous reinforcement for the use in building construction</b> <b>GM-FH2 (EN 15283-1) 15 mm</b>  <b>1508</b>	
Reaction to fire (for unprotected installation situations)	A1
Flexural strength (Bending breaking load)	L/II: 645 N - T/L: 252 N
Water vapour permeability (to control water vapour diffusion) specified as water vapour diffusion resistance	10
Thermal resistance specified as thermal conductivity	0.25 W/(m·K)
Impact resistance Airborne sound insulation Acoustic absorption	See system documentation of SAINT-GOBAIN RIGIPS GmbH or from the local supplier