

DECLARATION OF PERFORMANCE

No.: RigiMove_C_Modulprofil_75_LE_2504

(1) *Unique identification code of the product-type*
RigiMove_C_Modulprofil_75_LE_2504

(2) *Intended use/es*
**Metal framing component for gypsum plasterboard systems
C/51/75/51 (EN 14195) 75 mm**

(3) *Manufacturer*
**SAINT-GOBAIN RIGIPS GmbH
Willstätterstraße 60
D-40549 Düsseldorf**

(4) *Authorised representative*
N/A

(5) *System/s of AVCP*
System 4

(6a) *Harmonised standard*
EN 14195:2005/AC:2006

Notified body/ies
N/A

(6b) *European Assessment Document*
N/A

European Technical Assessment
N/A

Technical Assessment Body
N/A

Notified body/ies
N/A

(7) Declared performance/s

Essential characteristics	Performance
Reaction to fire (for unprotected installation situations)	A1
Flexural strength Yield strength	250 N/mm ²

(8) Appropriate Technical Documentation and/or Specific Technical Documentation
N/A

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Düsseldorf, 05. November 2025



Cordula Gudduschat, Managing Director



Dr. Benjamin Kaplan, Director R&D Isover/Rigips Germany

The above Declaration of Performance is valid for the following products:

Rigips RigiMove C-Modulprofil 75

Template for the CE marking to be affixed to the product:

CE	
SAINT-GOBAIN RIGIPS GmbH Willstätterstraße 60 D-40549 Düsseldorf 24	
Rigips_RigiMove_C_Modulprofil_75_LE_2504	
EN 14195:2005/AC:2006	
Metal framing component for gypsum plasterboard systems C/51/75/51 (EN 14195) 75 mm	
Reaction to fire (for unprotected installation situations)	A1
Flexural strength Yield strength	250 N/mm ²