

DECLARATION OF PERFORMANCE

No.: Rigips_U_Direktabhaenger_CD_65_125_200_C5_hoch_LE_2504

(1) *Unique identification code of the product-type*
Rigips_U_Direktabhaenger_CD_65_125_200_C5_hoch_LE_2504

(2) *Intended use/es*
**Suspended ceiling substructure component for indoor use in buildings
Suspension component (EN 13964)**

(3) *Manufacturer*
**SAINT-GOBAIN RIGIPS GmbH
Willstätterstraße 60
D-40549 Düsseldorf**

(4) *Authorised representative*
N/A

(5) *System/s of AVCP*
**System 3 for the load bearing capacity
System 4 for all other properties**

(6a) *Harmonised standard*
EN 13964:2014

Notified body/ies
Materialprüfungsamt Nordrhein-Westfalen MPA NRW (0432)

(6b) *European Assessment Document*
N/A

European Technical Assessment
N/A

Technical Assessment Body
N/A

Notified body/ies
N/A

(7) Declared performance/s

Essential characteristics	Performance
Reaction to fire	A1
Load bearing capacity	400 N
Resistance to fasteners	NPD
Durability	D

(8) Appropriate Technical Documentation and/or Specific Technical Documentation
N/A

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Düsseldorf, 05. November 2025



Cordula Gudduschat, Managing Director



Dr. Benjamin Kaplan, Director R&D Isover/Rigips Germany

The above Declaration of Performance is valid for the following products:

Rigips U Direktabhänger CD 65, 125, 200 C5-hoch

Template for the CE marking to be affixed to the product:

CE	
SAINT-GOBAIN RIGIPS GmbH Willstätterstraße 60 D-40549 Düsseldorf 14	
Rigips_U_Direktabhaenger_CD_65_125_200_C5_hoch_LE_2504	
EN 13964:2014 Suspended ceiling substructure component for indoor use in buildings Suspension component (EN 13964) 0432	
Reaction to fire	A1
Load bearing capacity	400 N
Durability	D