

## DECLARATION OF PERFORMANCE

No.: Rigips\_Winkelprofil\_50\_30\_07\_LE\_2504

(1) *Unique identification code of the product-type*  
**Rigips\_Winkelprofil\_50\_30\_07\_LE\_2504**

(2) *Intended use/es*  
**Metal framing component for gypsum plasterboard systems  
L/50/30 (EN 14195)**

(3) *Manufacturer*  
**SAINT-GOBAIN RIGIPS GmbH  
Willstätterstraße 60  
D-40549 Düsseldorf**

(4) *Authorised representative*  
**N/A**

(5) *System/s of AVCP*  
**System 4**

(6a) *Harmonised standard*  
**EN 14195:2005/AC:2006**

*Notified body/ies*  
**N/A**

(6b) *European Assessment Document*  
**N/A**

*European Technical Assessment*  
**N/A**

*Technical Assessment Body*  
**N/A**

*Notified body/ies*  
**N/A**

(7) Declared performance/s

| Essential characteristics                                     | Performance           |
|---------------------------------------------------------------|-----------------------|
| Reaction to fire<br>(for unprotected installation situations) | A1                    |
| Flexural strength<br>Yield strength                           | 240 N/mm <sup>2</sup> |

(8) Appropriate Technical Documentation and/or Specific Technical Documentation  
N/A

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Düsseldorf, 05. November 2025



Cordula Gudduschat, Managing Director



Dr. Benjamin Kaplan, Director R&D Isover/Rigips Germany

The above Declaration of Performance is valid for the following products:

**Rigips Winkelprofil 50/30-07**

Template for the CE marking to be affixed to the product:

|                                                                                                                                                             |                       |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------|
| <b>CE</b>                                                                                                                                                   |                       |
| <b>SAINT-GOBAIN RIGIPS GmbH</b><br><b>Willstätterstraße 60</b><br><b>D-40549 Düsseldorf</b><br><br><b>13</b><br><b>Rigips_Winkelprofil_50_30_07_LE_2504</b> |                       |
| <b>EN 14195:2005/AC:2006</b><br><br><b>Metal framing component for gypsum plasterboard systems</b><br><b>L/50/30 (EN 14195)</b>                             |                       |
| Reaction to fire<br>(for unprotected installation situations)                                                                                               | A1                    |
| Flexural strength<br>Yield strength                                                                                                                         | 240 N/mm <sup>2</sup> |