

DECLARATION OF PERFORMANCE

No.: RigiProfil_MultiTec_UD_28_LE_2504

- (1) *Unique identification code of the product-type*

RigiProfil MultiTec UD 28

RigiProfil MultiTec RiDuce UD 28

- (2) *Intended use/es*

Metal framing component for gypsum plasterboard systems

U/27/28/27 (EN 14195) 28 mm

- (3) *Manufacturer*

SAINT-GOBAIN RIGIPS GmbH

Willstätterstraße 60

D-40549 Düsseldorf

- (4) *Authorised representative*

N/A

- (5) *System/s of AVCP*

System 4

- (6a) *Harmonised standard*

EN 14195:2005/AC:2006

Notified body/ies

Internal

- (6b) *European Assessment Document*

N/A

European Technical Assessment

N/A

Technical Assessment Body

N/A

Notified body/ies

N/A

(7) Declared performance/s

Essential characteristics	Performance
Reaction to fire (R2F) (for unprotected installation situations)	A1
Flexural strength Yield strength	240 N/mm²

(8) Appropriate Technical Documentation and/or Specific Technical Documentation
N/A

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Düsseldorf, 03. April 2025



Cordula Gudduschat, Managing Director



Dr. Benjamin Kaplan, Director R&D Isover/Rigips Germany

CE	
SAINT-GOBAIN RIGIPS GmbH Willstätterstraße 60 D-40549 Düsseldorf	
13	
RigiProfil_MultiTec_UD_28_LE_2504	
EN 14195:2005/AC:2006	
Metal framing component for gypsum plasterboard systems U/27/28/27 (EN 14195) 28 mm	
Notified body/ies: N/A	
Reaction to fire (R2F) (for unprotected installation situations)	A1
Flexural strength	240 N/mm ²
Yield strength	