DECLARATION OF PERFORMANCE

No.: Rigidur_H_10_LE_2606

(1) *Unique identification code of the product-type*
Rigidur_H_10_LE_2606

(2) *Intended use/es*
Gypsum fibre board for the use in buildings
GF-C1-I-W2 (EN 15283-2) 10 mm

(3) *Manufacturer*
SAINT-GOBAIN RIGIPS GmbH
Willstätterstraße 60
D-40549 Düsseldorf

(4) *Authorised representative*
N/A

(5) *System/s of AVCP*
System 3 for reaction to fire
System 4 for all other properties

(6a) *Harmonised standard*
EN 15283-2:2008+A1:2009

Notified body/ies
Materialprüfungsamt Nordrhein-Westfalen (MPA NRW) (0432)

(6b) *European Assessment Document*
N/A

European Technical Assessment
N/A

Technical Assessment Body
N/A

Notified body/ies
N/A

(7) Declared performance/s

Essential characteristics		Performance
Reaction to fire **(for unprotected installation situations)**		**A2-s1, d0**
Shear strength **(for stiffening of timber frame outer walls and timber roof constructions)**		**NPD**
Flexural strength (Bending strength)		**≥ 5.5 N/mm²**
Water vapour permeability **(to control water vapour diffusion)** **specified as water vapour diffusion resistance**		**19**
Thermal resistance **specified as thermal conductivity**		**0.20 W/(m·K)**
Impact resistance	**(under end-use conditions)**	**See system documentation of SAINT-GOBAIN RIGIPS GmbH or from the local supplier (www.rigips.de)**
Airborne sound insulation		
Acoustic absorption		

(8) Appropriate Technical Documentation and/or Specific Technical Documentation
N/A

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Düsseldorf, 05. November 2025

Danijel Lučić, Managing Director

Stephan Behle, Director R&D ISOVER/RIGIPS, Germany

The above Declaration of Performance is valid for the following products:

Rigidur H 10

Template for the CE marking to be affixed to the product:

CE		
SAINT-GOBAIN RIGIPS GmbH **Willstätterstraße 60** **D-40549 Düsseldorf** **13** **Rigidur_H_10_LE_2606**		
EN 15283-2:2008+A1:2009 **Gypsum fibre board for the use in buildings** **GF-C1-I-W2 (EN 15283-2) 10 mm** 0432		
Reaction to fire (for unprotected installation situations)		A2-s1, d0
Flexural strength (Bending strength)		≥ 5.5 N/mm²
Water vapour permeability (to control water vapour diffusion) specified as water vapour diffusion resistance		19
Thermal resistance specified as thermal conductivity		0.20 W/(m·K)
Impact resistance	(under end-use conditions)	See system documentation of SAINT-GOBAIN RIGIPS GmbH or from the local supplier (www.rigips.de)
Airborne sound insulation		
Acoustic absorption		