

## Product data sheet

# Rigips wall profile UW 75 - C3-high / C4-high



**Product description:** Metal stud according to DIN 18182-1 / DIN EN 14195 made of sheet steel according to DIN EN 10346 with a coating according to DIN 55634. Material tolerances according to DIN EN 10143. Corrosion category C3-high / C4-high according to DIN EN ISO 12944.


**Area of application:** For the construction of substructures in wet and humid interior areas as well as for exterior applications.

						
Oberfläche glatt	Korrosionsschutz C3-C4	Anwendung Außenbereich	Anwendung Feuchtraum	Baustoffklasse A1	Blechdicke 0,6 mm	Lagerung

## Technische Daten

### Usage

For the construction of substructures in wet and humid interior areas as well as for exterior applications.

Parameters	Sign	Value	UOM	Drawing
<b>Dimensions</b>				
Metal thickness	t	0.6	mm	
Profile height	h	75.2	mm	
	Nominal	75	mm	
Profile width	b	39.8	mm	
	Nominal	40	mm	
Length	l	4.000	mm	
Profile parameter	$I_{yy}$	78.055	mm <sup>4</sup>	

Parameters	Sign	Value	Unit	Certification
<b>Material</b>				
Type of material		Coated sheet steel		EN 10169+ A1
Corrosion protection		C3-high - C4-high		EN ISO 12944
Corrosion Protection Class		C4		DIN 18219
Surface		Smooth		

The information in this publication is based on our current technical knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve the users of our products from the responsibility of carrying out their own inspections and tests, as they only represent general guidelines. They neither do imply any legally binding assurance of certain properties or of suitability for a particular application. It is the responsibility of those to whom we supply our products to ensure that any proprietary rights and existing laws and regulations are observed. We reserve the right to modifications in the interests of technical advancement without prior notice.

## Product data sheet

Rigips wall profile UW 75 - C3-high / C4-high

Parameters	Sign	Value	Unit	Certification
<b>Building material class</b>				
Fire behaviour		A1		EN 13501-1
<b>Colour</b>				
Colour		white		
<b>Notes</b>				
Storage		Dry Flat and level Air access		
Shelf Life		Unlimited		
Form of delivery		According to Pricelist		
Waste key		17 04 05		

The values listed in this product data sheet only reflect the performance characteristics of the products. In addition, gypsum plaster systems have structural and structural properties, which can be found in our system documentation (e. g. Planen und Bauen).

The information in this publication is based on our current technical knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve the users of our products from the responsibility of carrying out their own inspections and tests, as they only represent general guidelines. They neither do imply any legally binding assurance of certain properties or of suitability for a particular application. It is the responsibility of those to whom we supply our products to ensure that any proprietary rights and existing laws and regulations are observed. We reserve the right to modifications in the interests of technical advancement without prior notice.