


Product data sheet

Rigips reinforcing stud UA 50-2



Product description: Metal stud according to DIN 18182-1 / DIN EN 14195 made of sheet steel according to DIN EN 10346. Material tolerances according to DIN EN 10143.

Area of application: For the construction of substructures in gypsum plasterboard systems e.g. in reinforced door openings.



Oberfläche
glatt




Korrosions-
schutz



Anwendung
Innenraum



Baustoffklasse




Blechdicke



Lagerung

Technical specifications

| Parameters | Sign | Value | UOM | Drawing |
|-------------------|----------|-------------------------------------------------------------------------------------------|-----------------|---------------------------------------------------------------------------------------|
| Dimensions | | | | |
| Metal thickness | t | 2 | mm |  |
| Profile height | h | 48.8 | mm | |
| | Nominal | 50 | mm | |
| Profile width | b | 39.0 | mm | |
| | Nominal | 40 | mm | |
| Length | l | 2,600 / 2,750 / 3,000 / 3,250 / 3,500 / 3,750 / 4,000 / 4,250 / 4,500 / 5,000 | mm | |
| Profile parameter | I_{yy} | 101,616 | mm ⁴ | |

The information in this publication is based on our current technical knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve the users of our products from the responsibility of carrying out their own inspections and tests, as they only represent general guidelines. They neither do imply any legally binding assurance of certain properties or of suitability for a particular application. It is the responsibility of those to whom we supply our products to ensure that any proprietary rights and existing laws and regulations are observed. We reserve the right to modifications in the interests of technical advancement without prior notice.

Product data sheet

Rigips reinforcing stud UA 50-2

| Parameters | Sign | Value | Unit | Certification |
|--------------------------------|------|--------------------------------------------------|------|---------------|
| Material | | | | |
| Type of material | | Galvanised sheet steel | | EN 10346 |
| Material | | DX51D+Z | | |
| Corrosion protection | | Z100 | | EN 14195 |
| Surface | | Smooth | | |
| Building material class | | | | |
| Fire behaviour | | A1 | | EN 13501-1 |
| Miscellaneous | | | | |
| Additional Note | | Oblong perforation 8.2 x 40 mm, single row | | |
| Notes | | | | |
| Storage | | Dry Flat and level Air access | | |
| Shelf Life | | Unlimited | | |
| Form of delivery | | According to Pricelist | | |
| Waste key | | 17 04 05 | | |

The values listed in this product data sheet only reflect the performance characteristics of the products. In addition, gypsum plaster systems have structural and structural properties, which can be found in our system documentation (e. g. Planen und Bauen).

The information in this publication is based on our current technical knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve the users of our products from the responsibility of carrying out their own inspections and tests, as they only represent general guidelines. They neither do imply any legally binding assurance of certain properties or of suitability for a particular application. It is the responsibility of those to whom we supply our products to ensure that any proprietary rights and existing laws and regulations are observed. We reserve the right to modifications in the interests of technical advancement without prior notice.