

DECLARATION OF PERFORMANCE

No.: Rigidur_H_Activ_Air_125_LE_2202

SAINT-GOBAIN

- (1) *Unique identification code of the product-type*
Rigidur H Activ'Air 12.5
- (2) *Intended use/es*
**Gypsum fibre board for the use in buildings
GF-C1-I-W2 (EN 15283-2) 12.5 mm**
- (3) *Manufacturer*
**Saint-Gobain Rigips GmbH
Schanzenstr. 84
D-40549 Düsseldorf**
- (4) *Authorised representative*
N/A
- (5) *System/s of AVCP*
**System 3 for reaction to fire, shear strength, water vapour resistance factor
and thermal conductivity
System 4 for all other properties**
- (6a) *Harmonised standard*
EN 15283-2:2008+A1:2009
- Notified body/ies*
**Materialprüfanstalt für das Bauwesen und Produktionstechnik (MPA H) (0764)
VHT Institut für Leichtbau Trockenbau Holzbau GmbH (1503)
HFB Engineering GmbH (1034)**
- (6b) *European Assessment Document*
N/A
- European Technical Assessment*
N/A
- Technical Assessment Body*
N/A
- Notified body/ies*
N/A



(7) Declared performance/s


Essential characteristics	Performance
Reaction to fire (R2F) (for unprotected installation situations)	A2- s1,d0
Shear strength (↑↓) (for stiffening of timber frame outer walls and timber roof constructions)	1143 N
Flexural strength (Bending strength)	≥ 5.5 N/mm²
Water vapour permeability (to control water vapour diffusion) specified as water vapour diffusion resistance (μ)	19
Thermal resistance specified as thermal conductivity (λ)	0.20 W/(m·K)
Impact resistance Airborne sound insulation (R) Acoustic absorption (α)	See system documentation of Saint-Gobain Rigips GmbH or from the local supplier

(8) Appropriate Technical Documentation and/or Specific Technical Documentation
N/A


The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Düsseldorf, 03. February 2022



Raimund Heintl, Managing Director



Dr. Benjamin Kaplan, Director R&D Isover/Rigips Germany

CE

**Saint-Gobain Rigips GmbH
Schanzenstr. 84
D-40549 Düsseldorf**

13

Rigidur_H_Activ_Air_125_LE_2202

EN 15283-2:2008+A1:2009

**Gypsum fibre board for the use in buildings
GF-C1-I-W2 (EN 15283-2) 12.5 mm**

Notified body/ies: 0764, 1503, 1034

Reaction to fire (R2F) (for unprotected installation situations)	A2- s1,d0
Shear strength (↑↓) (for stiffening of timber frame outer walls and timber roof constructions)	1143 N
Flexural strength (Bending strength)	≥ 5.5 N/mm ²
Water vapour permeability (to control water vapour diffusion) specified as water vapour diffusion resistance (μ)	19
Thermal resistance specified as thermal conductivity (λ)	0.20 W/(m·K)
Impact resistance	See system documentation of Saint-Gobain Rigips GmbH or from the local supplier
Airborne sound insulation (R)	
Acoustic absorption (α)	

