

## DECLARATION OF PERFORMANCE

No.: Rigips\_Wandprofil\_CW\_125\_C3\_hoch\_C4\_hoch\_LE\_2311

(1) *Unique identification code of the product-type*  
**Rigips Wandprofil CW 125 C3-hoch C4-hoch**

(2) *Intended use/es*  
**Metal framing component for gypsum plasterboard systems  
C/50/125/50 (EN 14195) 125 mm**

(3) *Manufacturer*  
**SAINT-GOBAIN RIGIPS GmbH  
Schanzenstr. 84  
D-40549 Düsseldorf**

(4) *Authorised representative*  
**N/A**

(5) *System/s of AVCP*  
**System 4**

(6a) *Harmonised standard*  
**EN 14195:2005/AC:2006**

*Notified body/ies*  
**Internal**

(6b) *European Assessment Document*  
**N/A**

*European Technical Assessment*  
**N/A**

*Technical Assessment Body*  
**N/A**

*Notified body/ies*  
**N/A**

(7) Declared performance/s

Essential characteristics	Performance
Reaction to fire (R2F) (for unprotected installation situations)	A1
Flexural strength Yield strength	240 N/mm <sup>2</sup>

(8) Appropriate Technical Documentation and/or Specific Technical Documentation  
N/A


The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Düsseldorf, 05. December 2023



Cordula Gudduschat, Managing Director



Dr. Benjamin Kaplan, Director R&D Isover/Rigips Germany

	
<b>SAINT-GOBAIN RIGIPS GmbH</b> Schanzenstr. 84 D-40549 Düsseldorf	
<b>23</b>	
<b>Rigips_Wandprofil_CW_125_C3_hoch_C4_hoch_LE_2311</b>	
<b>EN 14195:2005/AC:2006</b>	
<b>Metal framing component for gypsum plasterboard systems</b> <b>C/50/125/50 (EN 14195) 125 mm</b> Notified body/ies: N/A	
Reaction to fire (R2F) (for unprotected installation situations)	A1
Flexural strength Yield strength	240 N/mm <sup>2</sup>

