

## **DECLARATION OF PERFORMANCE**

No.: **Rigips\_Wandprofil\_LWI\_60\_60\_06\_LE\_2202**

SAINT-GOBAIN

- (1) *Unique identification code of the product-type*  
**Rigips Wandprofil LWI 60/60-06**
- (2) *Intended use/es*  
**Metal framing component for gypsum plasterboard systems  
LWI/60/60-06 (EN 14195)**
- (3) *Manufacturer*  
**Saint-Gobain Rigips GmbH  
Schanzenstr. 84  
D-40549 Düsseldorf**
- (4) *Authorised representative*  
**N/A**
- (5) *System/s of AVCP*  
**System 4**
- (6a) *Harmonised standard*  
**EN 14195:2005/AC:2006**
- Notified body/ies*  
**Internal**
- (6b) *European Assessment Document*  
**N/A**

*European Technical Assessment*  
**N/A**

*Technical Assessment Body*  
**N/A**

*Notified body/ies*  
**N/A**



(7) Declared performance/s


Essential characteristics	Performance
<b>Reaction to fire (R2F)</b> (for unprotected installation situations)	<b>A1</b>
<b>Flexural strength</b> Yield strength	<b>240 N/mm<sup>2</sup></b>

(8) Appropriate Technical Documentation and/or Specific Technical Documentation  
N/A

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Düsseldorf, 04. February 2022



Raimund Heini, Managing Director



Dr. Benjamin Kaplan, Director R&D Isover/Rigips Germany



<b>CE</b>	
<b>Saint-Gobain Rigips GmbH</b> Schanzenstr. 84 D-40549 Düsseldorf	
<b>13</b>	
<b>Rigips_Wandprofil_LWI_60_60_06_LE_2202</b>	
<b>EN 14195:2005/AC:2006</b>	
<b>Metal framing component for gypsum plasterboard systems</b> <b>LWI/60/60-06 (EN 14195)</b>	
Notified body/ies: N/A	
Reaction to fire (R2F) (for unprotected installation situations)	A1
Flexural strength	240 N/mm <sup>2</sup>
Yield strength	

