

DECLARATION OF PERFORMANCE

No.: Rigidur_Ausgleichsschuettung_LE_2504

(1) *Unique identification code of the product-type*
Rigidur_Ausgleichsschuettung_LE_2504

(2) *Intended use/es*
**In-situ thermal insulation made of expanded clay lightweight aggregates
LD350-PS(1-5)-CR(1,4) (EN 14063-1)**

(3) *Manufacturer*
**SAINT-GOBAIN RIGIPS GmbH
Willstätterstraße 60
D-40549 Düsseldorf**

(4) *Authorised representative*
N/A

(5) *System/s of AVCP*
System 3

(6a) *Harmonised standard*
EN 14063-1:2004/AC:2006

Notified body/ies
Kiwa GmbH Niederlassung MPA Berlin-Brandenburg (0770)

(6b) *European Assessment Document*
N/A

European Technical Assessment
N/A

Technical Assessment Body
N/A

Notified body/ies
N/A

(7) Declared performance/s

Essential characteristics	Performance
Reaction to fire	A1
Grain size	1-5 mm
Bulk density	350 (+/- 67.5) kg/m ³
Water vapour diffusion	NPD
Residual grain strength	1.4 N/mm ²
Thermal resistance specified as thermal conductivity	0.1 W/(m·K)
Water permeability specified as water rise height	> 260 mm
Durability with regard to ageing/quality degradation	
- Reaction to fire	Will not change over time
- Thermal resistance	
- Compression strength	
Release of dangerous substances inside the building	NPD

(8) Appropriate Technical Documentation and/or Specific Technical Documentation
N/A

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Düsseldorf, 05. November 2025



Cordula Gudduschat, Managing Director



Dr. Benjamin Kaplan, Director R&D Isover/Rigips Germany

The above Declaration of Performance is valid for the following products:

Rigidur Ausgleichsschüttung

Template for the CE marking to be affixed to the product:

CE	
SAINT-GOBAIN RIGIPS GmbH Willstätterstraße 60 D-40549 Düsseldorf 24	
Rigidur_Ausgleichsschuettung_LE_2504 EN 14063-1:2004/AC:2006	
In-situ thermal insulation made of expanded clay lightweight aggregates LD350-PS(1-5)-CR(1,4) (EN 14063-1) 0770	
Reaction to fire	A1
Grain size	1-5 mm
Bulk density	350 (+/- 67.5) kg/m ³
Residual grain strength	1.4 N/mm ²
Thermal resistance specified as thermal conductivity	0.1 W/(m·K)
Water permeability specified as water rise height	> 260 mm
Durability with regard to ageing/quality degradation	
- Reaction to fire	Will not change over time
- Thermal resistance	
- Compression strength	