

DECLARATION OF PERFORMANCE

No.: Rigidur_H_Activ_Air_125_LE_2504

(1) *Unique identification code of the product-type*
Rigidur_H_Activ_Air_125_LE_2504

(2) *Intended use/es*
**Gypsum fibre board for the use in buildings
GF-C1-I-W2 (EN 15283-2) 12.5 mm**

(3) *Manufacturer*
**SAINT-GOBAIN RIGIPS GmbH
Willstätterstraße 60
D-40549 Düsseldorf**

(4) *Authorised representative*
N/A

(5) *System/s of AVCP*
**System 3 for reaction to fire, shear strength, water vapour resistance factor
and thermal conductivity
System 4 for all other properties**

(6a) *Harmonised standard*
EN 15283-2:2008+A1:2009

Notified body/ies
**Materialprüfanstalt für das Bauwesen und Produktionstechnik (MPA H) (0764)
VHT Institut für Leichtbau Trockenbau Holzbau GmbH (1503)
HFB Engineering GmbH (1034)**

(6b) *European Assessment Document*
N/A

European Technical Assessment
N/A

Technical Assessment Body
N/A

Notified body/ies
N/A

(7) Declared performance/s

Essential characteristics	Performance
Reaction to fire (for unprotected installation situations)	A2-s1, d0
Shear strength (for stiffening of timber frame outer walls and timber roof constructions)	1143 N
Flexural strength (Bending strength)	≥ 5.5 N/mm²
Water vapour permeability (to control water vapour diffusion) specified as water vapour diffusion resistance	19
Thermal resistance specified as thermal conductivity	0.20 W/(m·K)
Impact resistance Airborne sound insulation Acoustic absorption	See system documentation of SAINT-GOBAIN RIGIPS GmbH or from the local supplier

(8) Appropriate Technical Documentation and/or Specific Technical Documentation
N/A

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Düsseldorf, 05. November 2025



Cordula Gudduschat, Managing Director



Dr. Benjamin Kaplan, Director R&D Isover/Rigips Germany

The above Declaration of Performance is valid for the following products:

Rigidur H Activ'Air 12.5

Template for the CE marking to be affixed to the product:

CE	
SAINT-GOBAIN RIGIPS GmbH Willstätterstraße 60 D-40549 Düsseldorf 13 Rigidur_H_Activ_Air_125_LE_2504	
EN 15283-2:2008+A1:2009 Gypsum fibre board for the use in buildings GF-C1-I-W2 (EN 15283-2) 12.5 mm 0764, 1503, 1034	
Reaction to fire (for unprotected installation situations)	A2-s1, d0
Shear strength (for stiffening of timber frame outer walls and timber roof constructions)	1143 N
Flexural strength (Bending strength)	$\geq 5.5 \text{ N/mm}^2$
Water vapour permeability (to control water vapour diffusion) specified as water vapour diffusion resistance	19
Thermal resistance specified as thermal conductivity	0.20 W/(m·K)
Impact resistance Airborne sound insulation Acoustic absorption	See system documentation of SAINT-GOBAIN RIGIPS GmbH or from the local supplier