Product data sheet

Rigips Glasroc X Anschlussdichtung

Technical specifications

Parameters	Sign	Value	Unit	Certification
Material				
Type of material		High-Performance foam		
Filler / Plaster properties				
Processing temperature from		-10	°C	
Notes				
Storage		Dry Frost-free Air access Flat and level Shady		

The values listed in this product data sheet only reflect the performance characteristics of the products. In addition, gypsum plaster systems have structural and structural properties, which can be found in our system documentation (e. g. Planen und Bauen).

The information in this publication is based on our current technical knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve the users of our products from the responsibility of carrying out their own inspections and tests, as they only represent general guidelines. They neither do imply any legally binding assurance of certain properties or of suitability for a particular application. It is the responsibility of those to whom we supply our products to ensure that any proprietary rights and existing laws and regulations are observed. We reserve the right to modifications in the interests of technical advancement without prior notice.

Saint-Gobain Rigips GmbH • Willstätterstraße 60 • D-40549 Düsseldorf • Postfach 11 09 48 • D-40509 Düsseldorf
Tel +49 (0)211 5503-0 • Fax +49 (0)211 5503-208 • www.rigips.de • info@rigips.de